

MMM Group Limited
Suite 600 – 1455 West Georgia Street
Vancouver, BC V6G 2T3
t: 604-685-9381 | f: 604-683-8655

www.mmm.ca

June 14, 2010

File: 50-10751

City of Victoria
1 Centennial Square
Victoria, BC, V8W 1P6

Attention: Mr. Mike Lai, P.Eng.

Dear Mr. Lai

Reference: Traffic Operations Impact: Closure of one westbound lane on the Johnson Street Bridge

At your request, subsequent to the analysis completed in 2009, we have prepared this letter report that summarizes our analysis of the operational impacts predicted as a result of closing one of the two westbound traffic lanes on the Johnson Street Bridge. The purpose of the closure would be to reallocate the traffic lane into on-street westbound and eastbound bicycle lanes.

Our analysis was based on 2009 weekday PM peak hour traffic volumes provided by the City. The data was provided in the format of Synchro transportation analysis software files which included traffic volumes, pedestrian volumes and traffic signal timings. Our analysis was conducted using a combination on Synchro and SimTraffic transportation analysis. The use of these two separate tools allows us to obtain more confidence in the range of predicted results. In this sense, Synchro was used for the analysis of the conventional intersections and road segments, whereas SimTraffic was used to represent the impact of the lane drop beyond signalized intersections.

In the current configuration westbound traffic is loaded on to the Johnson Street Bridge from the Pandora Avenue / Store Street and Johnson Street / Wharf Street intersections. These two intersections share a single traffic signal controller which is programmed to activate the westbound signal phases sequentially. A simplified explanation of this can be described as the westbound green phase on Pandora Avenue / Store Street intersection will run while the north to westbound phase at the Johnson Street / Wharf Street intersection is red. Once the westbound Pandora Avenue phase goes to red, then the north to westbound green phase at the Johnson Street / Wharf Street will run. As the westbound phases of the two signals alternate, there is typically no conflict with these two traffic platoons attempting to merge together at the bridge end as they arrive at the bridge end at different times.

COMMUNITIES
TRANSPORTATION
BUILDINGS
INFRASTRUCTURE

June 14, 2010
City of Victoria
Mr. Mike Lai

TRAFFIC ANALYSIS

Existing Geometric Conditions (three lanes on the Johnson Street Bridge)

Pandora Street/Store Street Intersection – 2009 volumes (Synchro Results)

- This intersection operates at an overall intersection level of service (LOS) of C. The westbound approach is also expected to operate at LOS C and the southbound approach at LOS D.
- Traffic queues are no longer than 60 metres, thus indicating no traffic conflicts with adjacent intersections.

Johnson Street/Wharf Street Intersection – 2009 volumes (Synchro Results)

- This intersection operates at an overall intersection LOS D. The northbound left turn movement operates at LOS C and the southbound movement operates at LOS F.
- Traffic queues are no longer than 75 metres, thus indicating no traffic conflicts with adjacent intersections.

Pandora Street/Store Street Intersection – 2009 volumes (SimTraffic Results)

- This intersection operates at an overall intersection LOS of C. The westbound approach is also expected to operate at LOS C and the southbound approach is expected to operate at LOS E.
- Traffic queue on the westbound movement is no longer than 80 metres, thus indicating no traffic conflicts with Government Street intersections.

Johnson Street/Wharf Street Intersection – 2009 volumes (SimTraffic Results)

- This intersection operates at an overall intersection LOS C. The northbound left turn movement operates at LOS C and the southbound movement operates at LOS E.
- Traffic queues are no longer than 75 metres, thus indicating no traffic conflicts with adjacent intersections.

Two lane operation on the Johnson Street Bridge Scenario

Two scenarios were examined. One scenario removed the lane after the intersection signal and before the bridge end. The second scenario removed the lane on the approach to the intersection signal. The first scenario was evaluated through Synchro, whereas the second scenario made use of SimTraffic.

June 14, 2010
City of Victoria
Mr. Mike Lai

Pandora Street/Store Street Intersection – Lane removed after the intersection – 2009 volumes (SimTraffic analysis)

- Pandora Street westbound was reduced from two lanes at the Store Street intersection to one lane prior to the bridge end. This resulted in reducing the overall intersection level of service (LOS) from C to D. The westbound approach LOS was also reduced from LOS C to D.
- Traffic queues extended east along Pandora Street from Store Street approximately 110 metres. The simulation indicated that vehicles at the back of this queue would require two signal cycle lengths to clear the intersection. As a result, the LOS for these vehicles at the back of the queue would be reduced to LOS F.

Johnson Street/Wharf Street Intersection – Lane removed after the intersection – 2009 volumes (SimTraffic Analysis)

- The two north to west turning lanes at the Johnson Street/Wharf Street intersection were reduced to one lane prior to the bridge end. The overall LOS remained at LOS C while the north to west bound approach was reduced from LOS C to LOS D.
- Traffic queues extended south along Wharf Street from Johnson Street to south of the Yates Street intersection. The simulation indicated that the vehicles at the back of this queue would require two signal cycle lengths to clear the intersection. As a result, the LOS for those vehicles at the back of the queue would be reduced to LOS F.
- With the queue extending south through the Yates Street intersection, it is likely that the intersection will be blocked periodically. A blockage could affect west to south bound traffic turning vehicles from Yates Street and south to east bound turning vehicles from Wharf Street to Yates Street. Blockage of the Yates Street intersection will also extend through the crosswalk across Wharf Street at that location which may impact the safety for pedestrians. In addition, left turning traffic will use courtesy gaps but may not be able to adequately see southbound traffic, which may lead to safety concerns.

An area of additional delay was also observed. Under the current conditions, the westbound traffic from the Pandora Street/Store Street intersection clears onto the bridge before the north to west bound traffic from the Johnson Street/Wharf Street intersection arrives. This does not occur under the scenarios studied. The last vehicles in the west bound platoon from the Pandora Street/Store Street intersection must yield and wait for a gap in the traffic platoon arriving from the Johnson Street/Wharf Street intersection.